

# LIFTING TECHNOLOGY

## TWO POST LIFT

**MA STAR 3.5 A**  
VP 251232



### MA STAR 3.5 A

#### VP 251232

The 5-star lift MA STAR 3.5 A, which features stable torsion-resistant columns of rolled H-section steel, lifts cars and vans of up to 3.5 t. Symmetrical columns ensure that the lift width is kept to a minimum. The two post lift guarantees triple safety thanks to its spindle nut package, patented "giraffe" nut breakage detection and motor brake. The MA STAR also impresses with its straightforward plug and play commissioning as well as its intuitive, LED-based operation.

COMFORT version - options available.

#### PRODUCT DETAILS/ACCESSORIES

COMFORT version - options available  
(colour/sports car support arms/special voltage)

- RAL 5010 -

Description:

- Load capacity 3500 kg
- triple safety
- Columns turned by 45° for wide opening at the vehicle
- Asymmetrical support arms

\*Short support arms swivelling 180°

- Variable installation width
- High-quality powder coating:

- Gentian blu, RAL 5010 (columns)

- Anthracite grey, RAL 7016 (lifting carriages, support arms)

Scope of delivery:

- 2 asymmetrical columns with operating unit
- 4 asymmetrical support arms (2 double, 2 single telescopic)
- Support disc plug-in system
- Cable bridge
- Spindle oil (0.5 l)
- Operating instructions
- CE Declaration of Conformity
- Transport packaging

#### TECHNICAL DATA

Load capacity CE	3500 kg
Max. lifting height	1995 mm
Lifting / lowering time (depends on load)	approx. 40/40 s
Bottom clearance of the supportarms	100 mm
Adjustment range, support disc	80 - 110 mm
Extension range, short support arms	630 - 1240 mm
Extension range, long support arms	920 - 1490 mm
Overall width*	3592 mm
Outside base plates*	3351 mm
Outside columns*	3242 mm
Inside columns*	2660 mm
Drive-through width	2300 - 2450 mm
Column height	2943 mm
Max. overall height (with cable bridge)	4499 mm
Drive power	2 × 3.0 kW
Power supply	3/N/PE 400 V 50 Hz
Fuse	C16 A

