

HEAVY-DUTYTIRE CHANGER



MOBILE CONTROL UNIT

Wired remote control console allows one technician to safely monitor all tire changing operations.



EXTREMELY WIDE CLAMPING RANGE

Clamping range for rims of 14" to 58" without extensions; long jaws accommodate rims of high offset.



ADJUSTABLE MOUNTING TOOL

The adjustable mount/demount with bead-breaker disk and lever tool rotates 180 degrees to work on both sides of the tire.



PRESET TOOL CARRIAGE

The mount/demount tool travels from right to left of the tire for bead-breaking and mount/demount operation.

T8058



TECHNICAL SPECIFICATIONS

Max Rim Diameter	58" 147cm
Max Tire Width	99" 250cm
Max Rim Width	43" 110cm
Max Wheel Diameter	99" 250cm
Max Wheel Weight	3,200 lbs. 1,450 kg
Power Supply	208V 3Ph 60Hz
Dimensions HxWxD	80"x82"x118" 202x210x299cm

STANDARD ACCESSORIES

- Long Tire Lever
- Standard Tire Lever: 20" | 50cm
- Mounting Clamp
- · Bead pushing lever

OPTIONAL ACCESSORIES

- Clamp for Light Alloy Rims
- Earth Mover Clamp (OTR)
- · Tubeless Roller
- · Jaw protection kit





